ZELL Full Automatic AC1800

22.5l tank capacity 7" touch screen AC Machine with Printer

Easy and professional, This is the AC1800.
We put 3 loadcells for new oil,UV and used oil. The vacuum also measured by a seperate sensor.
The gas and oil database is updatable through a SD card.
The full animations and icons in UI make it is suitable for all users with different languages.

Model/Spec	AC1800
Refrigerant type	R134A (standard) or R1234yf (specific order)
Application	Petor Car
Max. P&Temp.	18 bar / 10-50 °C
Recovery	95%
Oil discharge	Auto
Vacuum & Test	Yes
A/C Leakage test	Yes with Sensor
PAG/POE/UV	Yes / No / Yes
GAS recharge	+/- 15g
Flushing	No
Air purge system	Yes
Car Plate	Yes
Languages	CN.EN.FR.DE.RU.ES.TR...
RTC	Yes
Database	Gas & oil
Software update	Yes
Front & rare wheels	10" / 4" Caster with lock
Service hoses	2.5 m / SEA J2196
Temp. sensor	Yes
HP & LP gauge	80 mm / Class1.0
HP & LP Transducer	No
Tank gauge	40 mm / Class1.0
Vacuum meter	Yes
Display / keypad	7" HQ / Capacitor Touch
Printer	Yes
Compressor	3/8 HP / 14cc
Fan & condenser	Yes
Vacuum pump	120 L /min, Dual stage
Tank capacity	22.5 L
Filter Drier	80 kg
Pump oil	50 hours
PAG/ POE/ UV bottle	PAG / UV 250ml
Drain oil bottle	250 ml
Gas scale	3g / 30 kg
PAG/ POE/ UV scale	PAG & UV 3g /30kg
Drain scale	3g /30kg
Categories	Refrigerant Charger, ZELL

ZELL Full Automatic AC1800F

10.1" touch screen full automatic AC machine with sight-glass Flushing and built-in printer



Model/Spec	AC1800F
Refrigerant type	R134A (standard) or R1234yf (specific order)
Application	Petor Car
Max. P&Temp.	18 bar / 10-50 °C
Recovery	95%
Oil discharge	Auto
Vacuum & Test	Yes
A/C Leakage test	Yes with Sensor
PAG/POE/UV	Yes / No / Yes
GAS recharge	+/- 15g
Flushing	Yes
Air purge system	Yes
Car Plate	Yes
Languages	CN.EN.FR.DE.RU.ES.TR...
RTC	Yes
Database	Gas & oil
Software update	Yes
Front & rare wheels	10" / 4" Caster with lock
Service hoses	2.5 m / SEA J2196
Temp. sensor	Yes
HP & LP gauge	80 mm / Class1.0
HP & LP Transducer	No
Tank gauge	40 mm / Class1.0
Vacuum meter	Yes
Display / keypad	10" HQ / Capacitor Touch
Printer	Yes
Compressor	1/2 HP / 14.2cc
Fan & condenser	Yes
Vacuum pump	120 L /min, Dual stage
Tank capacity	22.5 L
Filter Drier	80 kg
Pump oil	50 hours
PAG/ POE/ UV bottle	PAG / UV 250ml
Drain oil bottle	250 ml
Gas scale	3g / 30 kg
PAG/ POE/ UV scale	PAG & UV 3g /30kg
Drain scale	3g /30kg
Categories	Refrigerant Charger, ZELL

INTEREQUIP
INTEREQUIP PTY LTD.
www.interequip.com.au
E-mail: info@interequip.com.au
TEL: Australia 18000EQUIP (1800 037 847)